



Copper Alloy Terminals for improved electrical connections. • No exposed lead terminals. • Threaded insert terminals are recessed to prevent short circuits across battery connections. • No protruding or exposed vent valves. • Built in lifting handles on

many models. • Reinforced container walls to reduce bulging. • High Impact Strength Copolymer Polypropylene Case and Cover. • Completely Sealed Valve Regulated Construction. Won't leak! • Maintenance Free Design Never Requires Watering. • Absorbed Glass Mat (AGM) Micro-porous Glass Separators retain electrolyte. • UL Recognized Systems Component. • Low Self Discharge Rate Approximately 1 % per month • Operates in Extreme Temperatures. • Ships non HAZMAT. • Lead Acid Batteries are fully recyclable.



**ORDER FROM
AERO BATTERY**

Phone: (513) 271-9116
www.aerobattery.com
contact: info@erobattery.com

Part Number	Volts	Overall Dimensions						Unit Wt		Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 volts per cell							
		Length		Width		Height		Lbs	Kgs	1 Hour Rate	2 Hour Rate	4 Hour Rate	8 Hour Rate	24 Hour Rate	48 Hour Rate	72 Hour Rate	120 Hour Rate
		in	mm	in	mm	in	mm										
PVX-340T	12	7.71	196	5.18	132	6.89	175	25	11.4	21	27	28	30	34	36	37	38
PVX-420T	12	7.71	196	5.18	132	8.05	204	30	13.6	26	33	34	36	42	43	43	45
PVX-490T	12	8.99	228	5.45	138	8.82	224	36	16.4	31	39	40	43	49	52	54	55
PVX-560T	12	8.99	228	5.45	138	8.82	224	40	18.2	36	45	46	49	56	60	62	63
PVX-690T	12	10.19	259	6.60	168	8.93	227	51	23.2	42	53	55	60	69	73	76	79
PVX-840T	12	10.19	259	6.60	168	8.93	227	57	25.9	52	66	68	74	84	90	94	97
PVX-890T	12	12.90	328	6.75	172	8.96	228	62	28.2	55	70	72	79	89	95	98	102
PVX-1040HT	12	13.09	332	6.60	168	8.93	227	66	30.0	65	82	85	93	104	112	116	120
PVX-1040T	12	12.01	305	6.60	168	8.93	227	66	30.0	65	82	85	93	104	112	116	120
PVX-1080T	12	12.90	328	6.75	172	8.96	228	70	31.8	68	86	88	97	108	118	122	126
PVX-2120L	12	20.76	527	8.70	221	9.76	248	138	62.7	136	172	176	194	212	235	244	253
PVX-2580L	12	20.76	527	10.89	277	9.73	247	165	75	165	209	214	236	258	285	295	305
PVX-1030T	6	10.19	258.9	6.37	161.8	8.92	226.7	42	19.1	65	82	85	93	103	112	116	120
PVX-1380T	6	10.19	259	6.60	168	8.92	227	51	23.2	84	106	110	120	138	146	151	158
PVX-1680T	6	10.21	259	6.60	168	8.92	227	57	25.9	104	132	136	148	168	180	187	194
PVX-1780T	6	12.90	328	6.75	171	8.96	228	62	28.2	110	140	144	158	178	190	196	204
PVX-2080T	6	12.01	305	6.60	168	8.93	227	66	30.0	130	164	170	186	208	224	232	240
PVX-2160T	6	12.90	328	6.75	171	8.96	228	70	31.8	136	172	176	194	216	236	244	252
PVX-2240T	6	10.28	261.1	7.06	179.3	9.99	253.8	67	30.4	143	180	185	204	224	246	256	263
PVX-4140T	2	10.19	259	6.60	168	8.93	227	51	23.2	252	318	330	360	414	438	456	474
PVX-5040T	2	10.19	259	6.60	168	8.93	227	57	25.9	312	396	408	444	504	540	561	582
PVX-5340T	2	12.90	328	6.75	171	8.96	228	62	28.2	330	420	432	474	534	570	591	612
PVX-6240T	2	12.01	305	6.60	168	8.93	227	66	30.0	390	492	510	558	624	672	696	720
PVX-6480T	2	12.90	328	6.75	171	8.96	228	70	31.8	408	516	528	582	648	708	732	756